




Technical Specifications for Heaters



Type of Heater	 NDA01					 DA01		 DA03		 BA01				
Fuel	Gasoil					Gasoil		Gasoil		Petrol				
Approval number	ISRI 9047003935 –TA 1205005					ISRI 9047003935 –TA 1205005		ISRI 9047003935 – TA 1205005		ISRI 9047003935 –TA 1205005				
Voltage(V)	12 OR 24					12 OR 24		24		12				
Heat Flow(± 10%)(W)	BOOST	High	Medium	Low		High		Max	Min	BOOST	High	Medium	Low	
	2200	1800	1200	850		1800		5500	1200	2200	1800	1200	850	
Heater air flow (±10%) m3/h	BOOST	High	Medium	Low		73		Max	Min	BOOST	High	Medium	Low	
	85	73	51	51				216	186	85	73	51	51	
Fuel consumption (±10%) (L/h)	BOOST	High	Medium	Low		0.21		Max	Min	BOOST	High	Medium	Low	
	0.27	0.21	0.14	0.1				0.58	0.15	0.3	0.24	0.17	0.13	
Mean elect power in operation(W) 24V 12 V	Start	Boost	High	Medium	Low	Max	Min	Max	Min	Start	Boost	High	Medium	Low
	270	27	21	8.5	8.5	270	21	80	40	* Current at 12 V				
	250	30	21.5	9.6	9.6	250	21.5	* Current at 24 V		250	30	21.5	9.6	9.6
Size (mm)	360*133*125					360*133*125		525*194*179		360*133*125				